

LA401 | 雷龍氣動流體幫浦

AIR OPERATED FLUID PUMP

特點

- (1) 幫浦動作及抽油為兩個獨立系統，壓縮空氣不會汙染桶內油脂。
- (2) 典型的使用範圍為工廠、汽修廠、船舶保養、採礦機械、農耕、軍隊、建築、大眾運輸等。
- (3) 幫浦本體材質採用高強度鋁合金鍛造成型。

用油

- (1) 一般 00#~2# 黃油均能順暢注入。
- (2) 內附FP501壓力板，可搭配使用於較高黏度黃油或寒冷地區。

Feature

- (1) Pump moves and oil suction are two separation system, it won't contaminating grease.
- (2) Typically used in workshops, service stations, fleet maintenance, mining, agriculture, armed forces, construction, trains, etc.
- (3) The pump is made of aluminum alloy by forging.

Grease usage

- (1) General 00#~2# grease all can be infused into smoothly.
- (2) Included FP501 follower plate, can be used with higher viscosity grease or cold areas.



產品配件 Accessory

Index	品號 Parts No	品名 Item	LA401	LA501	LA601
A	LA200L	幫浦 Pump	●	●	●
B	FP401	桶蓋 Drum Cover	●	-	-
C	FP501	壓力板 Follower Plate	●	-	-
D	GH-220-TG	黃油管 Hose	●	●	-
E	G300	黃油槍 Grease Gun	●	●	-

型號 Model	容量 Capacity	空氣輸入壓力 Air Input Pressure	壓力比 Pressure Ratio	黃油輸出壓力 Grease Output Pressure	輸出量 Deliver Rate	油管長度 Hose Length	淨重 N.W.	毛重 G.W.	材積 CUFT
LA401	200L	4~9 bar 60~130 psi	45 : 1	180~405 bar 2700~5850 psi	9 g/cycle	20 ft	26.5 kgs	28.5 kgs	2.5'
LA501							14.5 kgs	15.5 kgs	1.2'
LA601						-	10.0 kgs	11.0 kgs	1.2'