

OF301 OF302

氣動機油幫浦 AIR OPERATED OIL PUMP

特點

- (1) 幫浦動作及抽油為兩個獨立系統，壓縮空氣不會汙染桶內油脂。
- (2) 典型的使用範圍為工廠、汽修廠、船舶保養、採礦機械、農耕、軍隊、建築、大眾運輸等。
- (3) 使用氣動幫浦，不須電力，可使用於有易燃物品的場所，如：加油站、汽車保養廠等場所。
- (4) 幫浦本體材質採用高強度鋁合金鍛造成型。

用油

- (1) 壓力比5:1適用於抽取 0#~120# 機油，及一般非腐蝕性溶劑。
- (2) 壓力比16:1適用於抽取 140#~200# 齒輪油，及一般非腐蝕性溶劑。
- (3) 若要知道所添加的油量，建議加購流量錶使用。(型號：M101、M201共二種可參考)
- (4) 若需延伸到較遠距離時，建議加購捲揚器使用。(型號：RE020)

Feature

- (1) Pump moves and oil suction are two separation system, it won't contaminating grease.
- (2) Typically used in workshops, service stations, fleet maintenance, mining, agriculture, armed forces, construction, trains, etc.
- (3) Use pneumatic pump, no need for electric power, can be used in places with flammable substances, such as, gas station, car maintenance plant etc.
- (4) The pump is made of aluminum alloy by forging.

Oil usage

- (1) Pressure ratio 5:1 suitable to pump 0#~120# engine oil or general non-corrosive solvent.
- (2) Pressure ratio 16:1 suitable to pump 140#~200# gear oil or general non-corrosive solvent.
- (3) If you want to know how much added oil volume is, we suggest you buy flow meter extra. (Model: M101, M201. There are two types for your option.)
- (4) If you want to pump the oil to long distance, we'd suggest hose reel be purchased extra. (Model: RE020)



| 型號 Model | 容量 Capacity | 空氣輸入壓力 Air Input Pressure | 壓力比 Pressure Ratio | 機油輸出壓力 Oil Output Pressure | 輸出量 Deliver Rate | 油管長度 Hose Length | 淨重 N.W. | 毛重 G.W. | 材積 CUFT |
|-------------|----------------|------------------------------|-----------------------|-------------------------------|---------------------|---------------------|------------|------------|------------|
| OF301 | 200L | 4~9 bar 60~130 psi | 5 : 1 | 20~45 bar 300~650 psi | 140 c.c./cycle | 20 ft | 15.6 kgs | 16.7 kgs | 1.2' |
| OF302 | | | 16 : 1 | 64~144 bar 960~2080 psi | 80 c.c./cycle | | 16.1 kgs | 17.2 kgs | |