



Pneumatic Lubricating Oil / Gear Oil Pump

Feature

- (1) Pump moves and oil suction are two separation system, it won't contaminating grease.
- (2) Typically used in workshops, service stations, fleet maintenance, mining, agriculture, armed forces, construction, trains, etc.
- (3) Use pneumatic pump, no need for electric power, can be used in places with flammable substances, such as, gas station, car maintenance plant etc.
- (4) The pump is made of aluminum alloy by forging.

Usage

- (1) OF301, OF501 suitable to pump 0#~120# engine oil or general non-corrosive solvent.
- (2) OF302 suitable to pump 140#~200# gear oil or general non-corrosive solvent.
- (3) If you want to know how much added oil volume is, we suggest you buy flow meter extra. (Model: M101, M201, M202 There are three types for your option.)
- (4) If you want to pump the oil to long distance, we'd suggest hose reel be purchased extra. (Model: RE020)

Model	Capacity	Air Input Pressure	Pressure Ratio	Oil Output Ppressure	Deliver Rate	Hose Length	N.W.	G.W.	CUFT
OF301	200L	4~9 bar 60~130 psi	5 : 1	20~45 bar 300~650 psi	140 c.c/cycle	20 ft	15.6 kgs	16.8 kgs	1.3'
OF302			16 : 1	64~144 bar 960~2080 psi	80 c.c/cycle		14.3 kgs	15.5 kgs	
OF501			1 : 1	4~9 bar 60~130 psi	150 c.c/cycle		8.6 kgs	10.0 kgs	1.1'