



OF201 / OF202
(40L)



OF205
(60L)

Pneumatic Lubricating Oil / Gear Oil Pump Feature

- (1) Pump moves and oil suction are two separation system, it won't contaminating grease.
- (2) Typically used in workshops, service stations, fleet maintenance, mining, agriculture, armed forces, construction, trains, etc.
- (3) Use pneumatic pump, no need for electric power, can be used in places with flammable substances, such as, gas station, car maintenance plant etc.
- (4) The pump is made of aluminum alloy.

Usage

- (1) OF201, OF205 are suitable for extracting #0-#120 engine oil and general non-corrosive solvents.
- (2) OF202 is suitable for extracting #140-#200 gear oil and general non-corrosive solvents.
- (3) To monitor the amount of oil dispensed, it is recommended to use a flow meter. (Model: M101, M201, M202)

Model	Capacity	Air Input Pressure	Pressure Ratio	Oil Output Pressure	Deliver Rate	Hose Length	N.W.	G.W.	CUFT
OF201	40L	4-9 bar 60-130 psi	5 : 1	20-45 bar 300-650 psi	140 c.c/cycle	10 ft	22.5 kgs	26.5 kgs	9.5'
OF202			16 : 1	64-144 bar 960-2080 psi	80 c.c/cycle				
OF205	60L		1 : 1	4-9 bar 60-130 psi	150 c.c/cycle		20.5 kgs	24.5 kgs	11.2'