

#### Accessory • Included × Not included

Index	Parts No	Item	LA401	LA501	LA601
A	LA200L	Pump	•	•	•
B	FP401	Drum Cover	•	×	×
C	FP501	Follower Plate	•	×	×
D	GH-220-TG	Hose	•	•	×
E	G300	Grease Gun	•	•	×

## LA401 / LA501 / LA601

### Air Operated Fluid Pump / Grease Pump

#### Feature

- (1) Pump moves and oil suction are two separation system, it won't contaminating grease.
- (2) Typically used in workshops, service stations, fleet maintenance, mining, agriculture, armed forces, construction, trains, etc.
- (3) The pump is made of aluminum alloy by forging.

#### Usage


- (1) General 00#~3# grease all can be infused into smoothly.
- (2) Included FP501 follower plate, can be used with higher viscosity grease or cold areas.

Model	Capacity	Air Input Pressure	Pressure Ratio	Grease Output Pressure	Deliver Rate	Hose Length	N.W.	G.W.	CUFT
LA401	200L	4~9 bar 60~130 psi	45 : 1	180~405 bar 2700~5850 psi	9 g/cycle	20 ft	26.5 kgs	28.5 kgs	2.5'
14.5 kgs							15.5 kgs	1.2'	
10.0 kgs							11.0 kgs		




## RE010 / RE020

### Hose Reels



Operation



Switching

Model	Applied to	Inlet	Outlet	N.W.	G.W.	Hose Length	Packing
RE010	Grease	1/4"	1/4"	19.2 kgs	20.2 kgs	1/4" x 15 M	Box
RE020	Oil	1/2"	1/2"	19.8 kgs	20.8 kgs	1/2" x 15 M	Box